



















8MP INFINITECOLOR TURRET CAMERA


8MP INFINITECOLOR TURRET CAMERA


Our Second Generation HD-TVI Series continues providing the quality expected from the AVYCON brand. This 8MP camera includes an upgraded Smart IR LED array, new DIP switch design for easily changing video formats (HD-TVI, CVI, AHD and Analog), and a sleek new magnetic ring designed to hide all mounting screws from view and create a seamless body look. With the newest generation chipset and board design, we have also increased power efficiency with a possible 20% savings in consumption. This camera also includes AoC(Audio over Coaxial) up to 22.9ft and a 2.8mm fixed Lens with Autofocus capabilities that can be controlled through the DVR . Also standard with this series is Digital NR, AGC, DWDR, and BLC capabilities along with IP67 outdoor rating.

FUNCTIONS

- · 8MP (3840 x 2160) @ 15fps
- · Max. Resolution: 3840 x 2160
- · True Day & Night ICR
- · Up to 98 ft. IR Illumination
- · Fixed 2.8mm Lens
- \cdot 2D DNR, Digital WDR, HLC, BLC
- · AoC(Audio over Coaxial) up to 22.9ft
- · Supports Remote Access with Windows, macOS, iOS and Android
- · Operating Temperature: -22°F 122°F
- · DC12V
- · NDAA Compliant

DIMENSIONS





OPTIONAL ACCESORIES



AVM-JB-BE-S1(-G)



AVM-CWM-EV-S1



AVM-HWM-E-S1
WALL MOUNT WITH



AVM-HCM-E-S1
CEILING MOUNT WITH
JUNCTION BOX



AVM-CRM-A1



AVM-POM-A1

SPECIFICATIONS

CAMERA	
	1/2.7" Progressive Scan CMOS
Resolution	
	3840 × 2160
Video Output	1-channel BNC Video Output
Image System	
Electronic Shutter Speed	Auto
IR Distance	
Video Formats	HD-TVI / AHD / CVI / CVBS(Analog)
Frame Rate	HD-TVI / AHD / CVI : 15 FPS
	CVBS Analog: 960H
Min. Illumination	0.05lux@F1.2(AGC ON),0Lux with IR ON
	fixed 2.8mm Lens
Angular Field of View	H:109.7° / V:57.6° / D:131.0°
Lens Mount	
S/N Ratio	
	OSD, Control over Coax (UTC)
IMAGE	
Day & Night	Color / Ext / BW (Black and White)
Digital WDR	
Digital Noise Reduction	
Auto Gain Control (AGC)	
Auto White Balance (AWB)	
Backlight Compensation (BLC)	
Edge Brightness Compensation	
Defoq	
HLC	
Sharpness	
Mirror Image	
Smart IR (Anti-SAT)	
Image Setting	
Defect Correction	
GENERAL	Auto / Walludi
	Audio over coaxial
Audio Range	
Angle Adjustment	
	DC 12V (±10%)
	IR OFF 50.8W. IR ON 54W
Ingress Protection	
	-22°~131° F (-30°~55° Celcius)
	-22 ~ 131 F (-50 ~ 35 CEICIUS) 3.93" x 2.56" (100 0mm x 65.0mm)
Difficusions	5.75 A 2.56 (100.0000)



MYCON

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon_aivo website: avycon.com