













FUNCTIONS

- 2MP (1920 x 1080)
- Motorized Varifocal 2.7-13.5mm Lens
- HD-TVI / CVI / AHD / CVBS (Analog)
- Easy-to-Use DIP Switch to Change Formats
- True Day / Night
- Smart IR Illumination Up to 115ft.
- Digital NR
- DWDR
- IP67 Outdoor Rating
- DC 12V (3W Consumption)
- NDAA Compliant


2MP HD-TVI VARIFOCAL TURRET CAMERA


2MP HD-TVI VARIFOCAL TURRET CAMERA WITH HD OVER COAX FEATURES

Our Second Generation HD-TVI Series continues providing the quality expected from the AVYCON brand. This 1080P camera includes an upgraded Smart IR LED array, new DIP switch design for easily changing video formats (HD-TVI, CVI, AHD and Analog), and a sleek new magnetic ring designed to hide all mounting screws from view and create a seamless body look. With the newest generation chipset and board design, we have also increased power efficiency with a possible 20% savings in consumption. This camera also includes a motorized 2.7mm--13.5mm Varifocal Lens with Autofocus capabilities that can be controlled through the DVR. Also standard with this series is Digital NR, AGC, DWDR, BLC, and Defog capabilities along with IP67 outdoor rating.

DIMENSIONS

Unit: inch (mm)





OPTIONAL ACCESSORIES



AVM-JB-BF-I 1 JUNCTION BOX



AVM-CWM-FDV-I 1



AVM-HWM-F-I 1 COMPACT WALL MOUNT HEAVY-DUTY WALL MOUNT



AVM-HCM-F-I 1 CEILING MOUNT



AVM-CRM-A1 CORNER MOUNT



POLE MOUNT

SPECIFICATIONS

000710110	
CAMERA	
	1/2.8" Progressive Scan CMOS
Resolution	
Image Size	1920 x 1080
	1-channel BNC Video Output
Image System	
Electronic Shutter	1/15s to 1/50,000s
IR Distance	Up to 115ft.
Video Formats	HD-TVI / AHD / CVI / CVBS (Analog)
Frame Rate	HD-TVI / AHD / CVI / CVBS (Analog): 30 FPS
Min. Illumination	0.01lux@F1.0(AGC ON),0Lux with IR ON
Lens	Motorized 2.7-13.5mm Lens
Lens Mount	φ14mm
Horizontal Field of View	115.9° (W) -33.8° (T)
S/N Ratio	39dB
	OSD, Control over Coax (UTC)
IMAGE	
	EXT / Auto / Color / BW (Black and White)
Digital WDR	
Digital NR	Yes (3D DNR)
Auto Gain Control (AGC)	Yes
	Yes
Backlight Compensation (BLC)	Yes
Edge Brightness Compensation	Yes
Defog	No
HLC	
Sharpness	
Mirror Image	
Smart IR (Anti-SAT)	
Image Setting	
Defect Correction	Auto / Manual
GENERAL	
Angle Adjustment	
	DC 12V (±10%)
Power Consumption	
Ingress Protection	
	-22F - 131F (-30°~55° Celcius)
Dimensions	Ø4.96" x 3.15" (Ø126.0mm x 80.0mm)

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon_aivo website: avycon.com