



AVN-W10-2P08W96G

NDAA | CE | FC

WEATHER PROOF OUTDOOR 8 PORT POE SWITCH

OVERVIEW

- IEEE802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3z, IEEE802.3af, IEEE802.3at
- 8 x 10/100/1000 Base-TX PoE Ports + 2 SFP (1G)
- 100-240VAC Input
- High back-plane bandwidth 4.8Gbps

DIMENSIONS

Unit: inch(mm)







OPTIONAL ACCESSORIES



AVM-ANCPM-U1 MOUNTING BRACKET



SPECIFICATIONS

ATTRIBUTE	
Networking Interfaces	8 x 10/100/1000 Mbps RJ45 Ethernet Ports
9	2 x 1Gbps SFP SLots
LED Indicators	Power, Link/Act, PoE
PERFORMANCE	
Switching Capacity	
Forwarding Capacity	14.88 Mpps
	Store and Forward
Packet Buffer Memory	2 Mbit
MAC Address Table	4K
PoE Budget	96W
PHYSICAL	
Dimension	295mm x 206mm x 50 mm
Weight	4lbs (1.8kg)
Operating Temperature	-20 to 60°C
Storage Temperature	-20 to 70°C
Operating Humidity	5 to 95% Noncondensing
Power Method	100-240VAC 50/60Hz
Max. Power Consumption	Including PoE Output: 96W
·	Excluding PoE Output: 10W
EMC Safety	FCC, CE, RoHS
POWER OVER ETHERNET	
PoE Interfaces	
PoE Standard	IEEE802.3af, IEEE802.3at
Max. PoE Wattage per Port	30W
PoE Voltage	
	V- (RJ45 Pin1,2), V+ (RJ45 Pin 3,6)
PACKAGE LIST	
PoE Switch	1each
User Manual	1each
Power Adapter	1each