



AVC-N4M81F360 AI

CE | FCC


8MP MULTI-SENSOR QUAD-DIRECTIONAL IR VANDAL DOME NETWORK CAMERA

OVERVIEW

- 8MP (3840 x 2160) @ 30fps
- Max. Resolution: 3840 x 2160
- One dome camera contains 4 sets of IP cameras, each to different direction
- Each module could circularly slide 0°~95°and vertically rotate 30°~70°
- Each module delivers max 2M (1920x1080P) full HD @25/30fps video stream
- Supports Smart H.265/H.264 Encoding
- True Day & Night ICR
- 360°(H)x90°(V) circular IR illumination, Up to 82 ft. IR Illumination
- 4.0mm lens x 4CH, F1.6
- Supports Remote Access with Windows, macOS, iOS and Android
- Support PoE+(802.3.at, class4) and DC24V / AC24V
- Built-in micro SD card slot with video and still image capture function (up to 256GB)

DIMENSIONS

Unit : inch(mm)



OPTIONAL ACCESSORIES



AVM-PT-CMT-N4M (included)
PENDANT CEILING
MOUNTING BRACKET



AVM-MT-WMT-F360
EXTENDED WALL
MOUNT BRACKET



AVM-MT-PMT-F360
EXTENDED WALL MOUNT
WITH POLE MOUNT BRACKET



AVM-MT-CMT-F360
EXTENDED WALL MOUNT
WITH CORNER MOUNT BRACKET



AVM-MT-WJB-F360
MOUNT WITH
JUNCTION BOX

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.8" Progressive Scan CMOS x 4CH
Resolution	8MP
Image Size	3840x2160
Min. Illumination	Color : 0.005Lux @ (F1.6, AGC ON) ; B/W : 0.001Lux @ (F1.6, AGC ON); 0Lux with IR
Shutter Speed	1/1 s – 1/100,000 s
IR Distance	Up to 82ft, 360°(H) x 90°(V)
Smart IR	Yes
Lens	4.0mm lens x 4CH, F1.6
Field of View	Horizontal: 90°, Vertical: 50°
VIDEO STREAM & AUDIO	
Max. Image Resolution	3840 x 2160 @ 30fps
Stream 0	Panoramic view: 3840x2160,2560x1440,1920x1080 (1~30fps)
Stream 1	CH1:1920x1080,1280x720,720x480 (1~30fps)
Stream 2	CH2:1920x1080,1280x720,720x480 (1~30fps)
Stream 3	CH1:1920x1080,1280x720,720x480 (1~30fps)
Stream 4	CH2:1920x1080,1280x720,720x480 (1~30fps)
Video Compression	H.265+/H.265/H.264+/H.264/MJPEG
Audio Compression	G.711 A/U
Live View	Up to 6 channels
User/Host	Up to 16 users, 3 levels: Administrator, Advanced User and Normal User
NETWORK	
Ethernet	1 x RJ45 10M / 100M
ONVIF	ONVIF(Profile S/G/T, 20.06)
Protocol	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP,DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP,DHCP, PPPoE RTMP (v5.x firmware and above)
Security	User authentication (ID and PW), Host authentication (MAC address); HTTPS encryption, IEEE802.1x port-based network access control; IP address filtering
IMAGE	
Day & Night	(Day/Night/Auto/Schedule)
Gain Control	Auto/Manual/Indoor/Outdoor
White Balance	Auto/Manual/Indoor/Outdoor
Privacy Mask	Off/On (1 Zone)
Sharpness	Yes
Image Setting	Yes
VIDEO ANALYTICS	
Smart Features	Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, SD full, SD error)
Smart Events	Up to 4 regions configurable: Human/vehicle detection and classification, Face comparison, Intrusion detection, Line crossing detection, Region entrance detection, Region exiting detection, Unattended baggage detection, Object removal detection, Scene change detection.
ROI	Up to 4 regions configurable
Alarm Link Events	Upload to FTP/Memory card, notify surveillance center, send email, trigger alarm output, trigger recording, trigger capture
Alarm	1CH alarm input; 1CH alarm output
Audio	1CH audio input; 1CH audio output
Built-In Storage	Micro SD/SDHC/SDXC Slot (up to 256GB) with video and still image capture function
GENERAL	
Power	AC24V,DC24V,PoE+ (802.3.at, class 4)
Working Temperature	-22 °F ~ 131 °F (-30°C ~ 55°C)
Protection	IP 66, IK10
Material	Aluminum Alloy; Plastic
Dimensions	Ø10.7" x 7" (Ø273mm x 180mm)
Weight	7.18lb (3.26Kg)